

Examcollection

<http://www.ipass4sure.com/examcollection.htm>



<http://www.ipass4sure.com>

312-38

ECCouncil

EC-Council Network Security Administrator

<http://www.ipass4sure.com/exams.asp?examcode=312-38>

The 312-38 practice exam is written and formatted by Certified Senior IT Professionals working in today's prospering companies and data centers all over the world! The 312-38 Practice Test covers all the exam topics and objectives and will prepare you for success quickly and efficiently. The 312-38 exam is very challenging, but with our 312-38 questions and answers practice exam, you can feel confident in obtaining your success on the 312-38 exam on your FIRST TRY!

ECCouncil 312-38 Exam Features

- Detailed questions and answers for 312-38 exam
- Try a demo before buying any ECCouncil exam
- 312-38 questions and answers, updated regularly
- Verified 312-38 answers by Experts and bear almost 100% accuracy
- 312-38 tested and verified before publishing
- 312-38 examcollection vce questions with exhibits
- 312-38 same questions as real exam with multiple choice options

Acquiring ECCouncil certifications are becoming a huge task in the field of I.T. More over these exams like 312-38 exam are now continuously updating and accepting this challenge is itself a task. This 312-38 test is an important part of ECCouncil certifications. We have the resources to prepare you for this. The 312-38 exam is essential and core part of ECCouncil certifications and once you clear the exam you will be able to solve the real life problems yourself. Want to take advantage of the Real 312-38 Test and save time and money while developing your skills to pass your ECCouncil 312-38 Exam? Let us help you climb that ladder of success and pass your 312-38 now!

DEMO EXAM

For Full Version visit

<http://www.ipass4sure.com/allexams.asp>

QUESTION: 1

John works as a C programmer. He develops the following C program:

```
#include <stdlib.h>
#include <stdio.h>
#include <string.h> int buffer(char *str) { char buffer1[10]; strcpy(buffer1, str); return 1;
}
int main(int argc, char *argv[]) { buffer (argv[1]); printf("Executed\n");
return 1;
}
```

His program is vulnerable to a _____ attack.

- A. SQL injection
- B. Denial-of-Service
- C. Buffer overflow
- D. Cross site scripting

Answer: C

Explanation:

This program takes a user-supplied string and copies it into 'buffer1', which can hold up to 10 bytes of data. If a user sends more than 10 bytes, it would result in a buffer overflow.

QUESTION: 2

Drag and drop the terms to match with their descriptions.

	Terms	Description
Backdoor	Place Here	It is a malicious software program that contains hidden code and masquerades itself as a normal program.
Spamware	Place Here	It is a technique used to determine which of a range of IP addresses map to live hosts.
Ping sweep	Place Here	It is software designed by or for spammers to send out automated spam e-mail.
Trojan horse	Place Here	It is any program that allows a hacker to connect to a computer without going through the normal authentication process.

Answer:

	Terms	Description
Backdoor	Trojan horse	It is a malicious software program that contains hidden code and masquerades itself as a normal program.
Spamware	Ping sweep	It is a technique used to determine which of a range of IP addresses map to live hosts.
Ping sweep	Spamware	It is software designed by or for spammers to send out automated spam e-mail.
Trojan horse	Backdoor	It is any program that allows a hacker to connect to a computer without going through the normal authentication process.

Explanation:

Following are the terms with their descriptions:

Terms	Description
Trojan horse	It is a malicious software program that contains hidden code and masquerades itself as a normal program.
Ping sweep	It is a technique used to determine which of a range of IP addresses map to live hosts.
Spamware	It is software designed by or for spammers to send out automated spam e-mail.
Backdoor	It is any program that allows a hacker to connect to a computer without going through the normal authentication process.

A Trojan horse is a malicious software program that contains hidden code and masquerades itself as a normal program. When a Trojan horse program is run, its hidden code runs to destroy or scramble data on the hard disk. An example of a Trojan horse is a program that masquerades as a computer logon to retrieve user names and password information. The developer of a Trojan horse can use this information later to gain unauthorized access to computers. Trojan horses are normally spread by e-mail attachments. Ping sweep is a technique used to determine which of a range of IP addresses map to live hosts. It consists of ICMP ECHO requests sent to multiple hosts. If a given address is live, it will return an ICMP ECHO reply. A ping is often used to check that a network device is functioning. To disable ping sweeps on a network, administrators can block ICMP ECHO requests from outside sources. However, ICMP TIMESTAMP and ICMP INFO can be used in a similar manner. Spamware is software designed by or for spammers to send out automated spam e-mail. Spamware is used to search for e-mail addresses to build lists of e-mail addresses to be used either for spamming directly or to be sold to spammers. The spamware package also includes an e-mail harvesting tool. A backdoor is any program that allows a hacker to connect to a computer without going through the normal authentication process. The main advantage of this type of attack is that the network traffic moves from inside a network to the hacker's computer. The traffic moving from inside a network to the outside world is typically the least restrictive, as companies are more concerned about what comes into a network, rather than what leaves it. It, therefore, becomes hard to detect backdoors.

QUESTION: 3

Fill in the blank with the appropriate term. ----- is the complete network configuration and information toolkit that uses multi-threaded and multi-connection technologies in order to be very fast and efficient.

Answer: NetRanger

Explanation:

NetRanger is the complete network configuration and information toolkit that includes the following tools: a Ping tool, Trace Route tool, Host Lookup tool, Internet time synchronizer, Whois tool, Finger Unix hosts tool, Host and port scanning tool, check multiple POP3 mail accounts tool, manage dialup connections tool, Quote of the day tool, and monitor Network Settings tool. These tools are integrated in order to use an application interface with full online help. NetRanger is designed for both new and experienced users. This tool is used to help diagnose network problems and to get information about users, hosts, and networks on the Internet or on a user computer network. NetRanger uses multi-threaded and multi-connection technologies in order to be very fast and efficient.

QUESTION: 4

Fill in the blank with the appropriate term. A _____ device is used for uniquely recognizing humans based upon one or more intrinsic physical or behavioral traits.

Answer: biometric

Explanation:

A biometric device is used for uniquely recognizing humans based upon one or more intrinsic, physical, or behavioral traits. Biometrics is used as a form of identity access management and access control. It is also used to identify individuals in groups that are under surveillance. Biometric characteristics can be divided into two main classes:

1. Physiological: These devices are related to the shape of the body. These are not limited to the fingerprint, face recognition, DNA, hand and palm geometry, and iris recognition, which has largely replaced the retina and odor/scent. 2. Behavioral: These are related to the behavior of a person. They are not limited to the typing rhythm, gait, and voice.

QUESTION: 5

Which of the following analyzes network traffic to trace specific transactions and can intercept and log traffic passing over a digital network? Each correct answer represents a complete solution. Choose all that apply.

A. Wireless sniffer

- B. Spectrum analyzer
- C. Protocol analyzer
- D. Performance Monitor

Answer: C, A

Explanation:

Protocol analyzer (also known as a network analyzer, packet analyzer or sniffer, or for particular types of networks, an Ethernet sniffer or wireless sniffer) is computer software or computer hardware that can intercept and log traffic passing over a digital network. As data streams flow across the network, the sniffer captures each packet and, if needed, decodes and analyzes its content according to the appropriate RFC or other specifications. Answer option D is incorrect. Performance Monitor is used to get statistical information about the hardware and software components of a server. Answer option B is incorrect. A spectrum analyzer, or spectral analyzer, is a device that is used to examine the spectral composition of an electrical, acoustic, or optical waveform. It may also measure the power spectrum.

QUESTION: 6

In which of the following conditions does the system enter ROM monitor mode? Each correct answer represents a complete solution. Choose all that apply.

- A. The router does not have a configuration file.
- B. There is a need to set operating parameters.
- C. The user interrupts the boot sequence.
- D. The router does not find a valid operating system image.

Answer: D, C

Explanation:

The system enters ROM monitor mode if the router does not find a valid operating system image, or if a user interrupts the boot sequence. From ROM monitor mode, a user can boot the device or perform diagnostic tests. Answer option A is incorrect. If the router does not have a configuration file, it will automatically enter Setup mode when the user switches it on. Setup mode creates an initial configuration. Answer option B is incorrect. Privileged EXEC is used for setting operating parameters.

QUESTION: 7

Which of the following protocols is used for exchanging routing information between two gateways in a network of autonomous systems?

- A. IGMP

- B. ICMP
- C. EGP
- D. OSPF

Answer: C

Explanation:

EGP stands for Exterior Gateway Protocol. It is used for exchanging routing information between two gateways in a network of autonomous systems. This protocol depends upon periodic polling with proper acknowledgements to confirm that network connections are up and running, and to request for routing updates. Each router requests its neighbor at an interval of 120 to 480 seconds, for sending the routing table updates. The neighbor host then responds by sending its routing table. EGP-2 is the latest version of EGP. Answer option B is incorrect. Internet Control Message Protocol (ICMP) is a maintenance protocol that allows routers and host computers to swap basic control information when data is sent from one computer to another. It is generally considered a part of the IP layer. It allows the computers on a network to share error and status information. An ICMP message, which is encapsulated within an IP datagram, is very useful to troubleshoot the network connectivity and can be routed throughout the Internet. Answer option A is incorrect. Internet Group Management Protocol (IGMP) is a communication protocol that multicasts messages and information among all member devices in an IP multicast group. However, multicast traffic is sent to a single MAC address but is processed by multiple hosts. It can be effectively used for gaming and showing online videos. IGMP is vulnerable to network attacks. Answer option D is incorrect. Open Shortest Path First (OSPF) is a routing protocol that is used in large networks. Internet Engineering Task Force (IETF) designates OSPF as one of the Interior Gateway Protocols. A host uses OSPF to obtain a change in the routing table and to immediately multicast updated information to all the other hosts in the network.

QUESTION: 8

Which of the following is a 16-bit field that identifies the source port number of the application program in the host that is sending the segment?

- A. Sequence Number
- B. Header Length
- C. Acknowledgment Number
- D. Source Port Address

Answer: D

Explanation:

Source Port Address is a 16-bit field that identifies the source port number of the application program in the host that is sending the segment. Answer option C is incorrect. This is a 32-bit field that identifies the byte number that the sender of the segment is expecting to receive from the receiver. Answer option B is incorrect. This is a 4-bit field

that defines the 4-byte words in the TCP header. The header length can be between 20 and 60 bytes. Therefore, the value of this field can be between 5 and 15. Answer option A is incorrect. This is a 32-bit field that identifies the number assigned to the first byte of data contained in the segment.

QUESTION: 9

Fill in the blank with the appropriate term. _____ is typically carried out by a remote attacker attempting to gain information or access to a network on which it is not authorized or allowed.

Answer: Network reconnaissance

Explanation:

Network reconnaissance is typically carried out by a remote attacker attempting to gain information or access to a network on which it is not authorized or allowed. Network reconnaissance is increasingly used to exploit network standards and automated communication methods. The aim is to determine what types of computers are present, along with additional information about those computers such as the type and version of the operating system. This information can be analyzed for known or recently discovered vulnerabilities that can be exploited to gain access to secure networks and computers. Network reconnaissance is possibly one of the most common applications of passive data analysis. Early generation techniques, such as TCP/IP passive fingerprinting, have accuracy issues that tended to make it ineffective. Today, numerous tools exist to make reconnaissance easier and more effective.

QUESTION: 10

Fill in the blank with the appropriate term. The _____ is an application layer protocol that is used between workstations and routers for transporting SNA/NetBIOS traffic over TCP sessions.

Answer: DCAP

Explanation:

The Data Link Switching Client Access Protocol (DCAP) is an application layer protocol that is used between workstations and routers for transporting SNA/NetBIOS traffic over TCP sessions. It was introduced in order to address a few deficiencies by the Data Link Switching Protocol (DLSw). The DLSw raises the important issues of scalability and efficiency, and since DLSw is a switch-to-switch protocol, it is not efficient when implemented on workstations. DCAP was introduced in order to address these issues.

QUESTION: 11

John works as a professional Ethical Hacker. He has been assigned the project of testing the security of www.we-are-secure.com. He is using a tool to crack the wireless encryption keys. The description of the tool is as follows:



Pass4sure Certification Exam Features;

- Pass4sure offers over **2500** Certification exams for professionals.
- More than **98,800** Satisfied Customers Worldwide.
- Average **99.8%** Success Rate.
- Over **120** Global Certification Vendors Covered.
- Services of **Professional & Certified Experts** available via support.
- Free **90 days** updates to match real exam scenarios.
- **Instant Download Access!** No Setup required.
- Price as low as **\$19**, which is 80% more **cost effective** than others.
- **Verified answers** researched by industry experts.
- Study Material **updated** on regular basis.
- Questions / Answers are downloadable in **PDF** format.
- Mobile Device Supported (**Android, iPhone, iPod, iPad**)
- **No authorization** code required to open exam.
- **Portable** anywhere.
- **Guaranteed Success.**
- **Fast**, helpful support **24x7**.



View list of All certification exams offered;
<http://www.ipass4sure.com/allexams.asp>

View list of All Study Guides (SG);
<http://www.ipass4sure.com/study-guides.asp>

View list of All Audio Exams (AE);
<http://www.ipass4sure.com/audio-exams.asp>

Download Any Certification Exam DEMO.
<http://www.ipass4sure.com/samples.asp>

To purchase Full version of exam click below;
<http://www.ipass4sure.com/allexams.asp>

3COM	CompTIA	Filemaker	IBM	LPI	OMG	Sun
ADOBE	ComputerAssociates	Fortinet	IISFA	McAfee	Oracle	Sybase
APC	CWNP	Foundry	Intel	McData	PMI	Symantec
Apple	DELL	Fujitsu	ISACA	Microsoft	Polycom	TeraData
BEA	ECCouncil	GuidanceSoftware	ISC2	Mile2	RedHat	TIA
BICSI	EMC	HDI	ISEB	NetworkAppliance	Sair	Tibco
CheckPoint	Enterasys	Hitachi	ISM	Network-General	SASInstitute	TruSecure
Cisco	ExamExpress	HP	Juniper	Nokia	SCP	Veritas
Citrix	Exin	Huawei	Legato	Nortel	See-Beyond	Vmware
CIW	ExtremeNetworks	Hyperion	Lotus	Novell	Google	

and many others.. See complete list [Here](#)

